





1K Profi Primer Filler Aerosol

product information

02-11-2023 V1

Site 1 von 1

Professional product for priming and filling scratches and cracks in one operation, can be used universally and is easy to sand. Due to the high solids content, pores and sanding grooves are evened out and a closed, smooth surface is achieved. Excellent adhesion to sanded steel sheet, galvanized coatings, old paint, polyester filler, PVC, PPO/PA, ABS, ABS/PC and PC/PBT.

Color	grey and redbrown
Dilution	Ready for use
Drying	temperature 20°C
dust dry	3 - 4 min.
dry to touch	8-10 min.
ready for sanding	20 min.
Spray passes	1-3 spray coats (up to 150 µm)
Flash off time	5 – 10 min. between the spray coats
Spraying distance	10 – 15 cm
	dry, P500 – P800 wet, P500 – P800
	dry, P360 – P500
VOC-Regulation	2004/42/IIIB(e)(840)<711

Notes:

Substrates should be clean, dust-free and dry.



Shake can thoroughly for at least 2 minutes from when the mixing balls are heard.



After painting, turn the can upside down and spray the valve until empty.

Processing conditions: From + 20°C

Storage: Can be stored well closed in cool, dry rooms for 5 years.

This product sheet is for information purposes only ! To the best of our knowledge, the information given here corresponds to the state of the art and is based on many years of experience in the manufacture of our products. However, the information is nonbinding and without guarantee.