



7536 Aluminium Spachtel (Putty)

product information



25.04.2024 V1

AP-Merit 7536 Aluminum putty is an aluminum pigmented polyester-based putty. This product is suitable for filling dents and irregularities on iron and steel, GRP and wood. Good sandability, high vertical stability and high flexibility. Not suitable for aluminium or galvanized surfaces!

Features

Colour:	silvergrey-metallic
Mixing ratio:	100 : 2-3
Hardener:	BPO hardener tube (red, blue or white)
Thinner:	not required




Processing

	At 20°C approx. 4-5 min		Polyester-based
---	-------------------------	---	-----------------


Drying



	20 Min.		10 Min.
---	---------	---	---------

Further processing

	Dry P150-240
	Dry P150-240
	Insulate with 1K or 2K fillers before recoating

Notes

	<ul style="list-style-type: none">- The substrate must be clean, dry and free of grease. Sand the surface- Remove uncured old paintwork or primers- Do not use on thermoplastic or acidic products (reaction primers)
---	---

	<ul style="list-style-type: none"> - Over-curing can lead to discoloration of the topcoat! - Processing temperature: from + 10°C - For filling work on non-ferrous metal surfaces (e.g. aluminium, galvanized surfaces), primer must be applied in advance to ensure optimum adhesion.
	<p>Store in a dry and frost-free place. Can be stored for at least 12 months in the sealed original container.</p>
	<p>2004/42/IB(b)(250)<250</p>
<p><small>This data sheet is for information purposes only! To the best of our knowledge, the information corresponds to the state of the art and is based on many years of experience in the manufacture of our products. However, the information is non-binding and without guarantee.</small></p>	

Wolfgang GesmbH. – www.ap-merit.com – office@ap-merit.com -Tel.: +43 5576 72330