





# Multi Putty PLUS 7530-4

## Product-Information

24-10-2020 V1

page 1 of 1

AP-Merit 7530-4 Multi Putty PLUS is a multifunctional polyester with adhesion on steel sheet, galvanized sheet metal, aluminum, tinned surfaces, GRP and wood. 7530-4 is easy to apply without pores, has a short drying time and can be easily sanded manually or mechanically. Processing with dry sanding. No clogging of the sanding paper!

<b>Shade</b>	beige
<b>Dosing</b>	100 gr. putty + 2-3 gr. hardener
<b>Hardener</b>	BPO hardener paste red or blue
<b>Pot Life</b>	3 -4 minutes
<b>Drying Time</b>	sandable
Temperature +20°C	20 minutes
Temperature +60°C	5 minutes
	dry, P150 - P320
	dry, P150 - P400
<b>VOC content</b>	2004/42/IIIB (b) (250) < 250g/l Delivery viscosity at 20°C: as a paste Density: 1,97 – 1,99 g/cm³

### Notes:

#### Handling/Application:

- the surface must be cleaned, dried, degreased and matted
- Mix putty thoroughly with 2-3% hardener BPO and apply within 4-6 minutes at 20°C
- higher temperatures can shorten the pot life and accelerate drying
- after drying, 7530-4 Multi Putty PLUS can be painted over with all commercially available paint systems

Processing conditions: From + 15°C

Overdosing of the hardener paste is to be avoided. Bleeding-through and colour changes in the finishing coat might be the result.

Storage: Store dry and frost-free. Can be stored for at least 1 year in closed original container

This product sheet is for information purposes only ! To the best of our knowledge, the information given here corresponds to the state of the art and is based on many years of experience in the manufacture of our products. However, the information is non-binding and without guarantee.