

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *AP-Merit 7525 Härter standard*
- **UFI:** *RF30-M0MC-3004-9PS5*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Hardening agent/ Curing agent*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Wolfgang GesmbH
Barnabas-Fink-Str. 11
A- 6845 Hohenems
Tel : +43 (0) 5576 / 72330
eMail: office@ap-merit.com*
- **1.4 Notrufnummer:** *Vergiftungsinformationszentrale Wien +43 (0)1 4064343*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226 *Flammable liquid and vapour.*



Acute Tox. 4 H332 *Harmful if inhaled.*

Skin Sens. 1 H317 *May cause an allergic skin reaction.*

STOT SE 3 H335-H336 *May cause respiratory irritation. May cause drowsiness or dizziness.*

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** *Warning*
- **Hazard-determining components of labelling:**
*Hexamethylene diisocyanate, oligomers
2-Butoxyethyl acetate
n-Butyl acetate
2-Methoxy-1-methylethyl acetate*
- **Hazard statements**
*H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.*

(Contd. on page 2)

Trade name: AP-Merit 7525 Härter standard

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.

Additional information:

- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction.
- Restricted to professional users.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients
3.2 Chemical characterisation: Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17	Hexamethylene diisocyanate, oligomers ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-25%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	5-<10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures
General information:

- Immediately remove any clothing soiled by the product.
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- In case of irregular breathing or respiratory arrest provide artificial respiration.

After inhalation:

- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately rinse with water.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Trade name: AP-Merit 7525 Härter standard

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Nitrogen oxides (NO_x)
Carbon monoxide (CO)
Hydrogen cyanide (HCN)
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.
Decontaminate immediately with suitable mixture (flammable):
 - as such usable (inflammatory!):

water	45 Vol. %
ethanol or isopropanol	50 Vol. %
ammonia solution (Density= 0.88)	5 Vol. %
 - alternatively (non-flammable):

sodium carbonate	5 Vol. %
water	95 Vol. %
 Add the same decontaminant to any residues and allow to stand for several days in an non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only be employed in processes in which this product is used under appropriate medical supervision.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Trade name: AP-Merit 7525 Härter standard

(Contd. of page 3)

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:**

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

Store away from foodstuffs.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.

· **Storage class: 3**

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

28182-81-2 Hexamethylene diisocyanate, oligomers

EBW	Short-term value: 0.5 mg/m ³ exposition evaluation value TRGS 430 (EBW)
-----	---

123-86-4 n-Butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

108-65-6 2-Methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm
Sk	

112-07-2 2-Butoxyethyl acetate

WEL	Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm
Sk	

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Trade name: AP-Merit 7525 Härter standard

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	124-128 °C

· **Flash point:** 27 °C (DIN 53213)

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 280 °C (DIN 51794)

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:	1.2 Vol %
Upper:	10.8 Vol %

· **Vapour pressure at 20 °C:** 10.7 hPa

· **Density at 20 °C:** 1.036 g/cm³ (DIN 53217)

· **Relative density** Not determined.

· **Vapour density** Not determined.

(Contd. on page 6)

Trade name: AP-Merit 7525 Härter standard

(Contd. of page 5)

· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with water:	<i>Not miscible or difficult to mix.</i>
· Partition coefficient: n-octanol/water:	<i>Not determined.</i>
· Viscosity: Dynamic: Kinematic at 20 °C:	<i>Not determined.</i> <i>10-15 s (DIN 53211/4)</i>
· Solvent content: VOC (EC)	<i>45.99 %</i>
Solids content (weight-%):	<i>54.0 %</i>
· 9.2 Other information	<i>No further relevant information available.</i>

SECTION 10: Stability and reactivity

- **10.1 Reactivity** *No further relevant information available.*
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **10.3 Possibility of hazardous reactions** *No dangerous reactions known.*
- **10.4 Conditions to avoid** *No further relevant information available.*
- **10.5 Incompatible materials:** *No further relevant information available.*
- **10.6 Hazardous decomposition products:**
Possible in traces.
Nitrogen oxides
Hydrogen chloride (HCl)
Hydrogen cyanide (prussic acid)
Carbon monoxide
Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Harmful if inhaled.
- **Primary irritant effect:**
- **Skin corrosion/irritation** *Based on available data, the classification criteria are not met.*
- **Serious eye damage/irritation** *Based on available data, the classification criteria are not met.*
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** *Based on available data, the classification criteria are not met.*
- **Carcinogenicity** *Based on available data, the classification criteria are not met.*
- **Reproductive toxicity** *Based on available data, the classification criteria are not met.*
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** *Based on available data, the classification criteria are not met.*
- **Aspiration hazard** *Based on available data, the classification criteria are not met.*

GB

(Contd. on page 7)

Trade name: AP-Merit 7525 Härter standard

(Contd. of page 6)



SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) : slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|-------------------------------|
| · 14.1 UN-Number | UN1263 |
| · ADR, IMDG, IATA | |
| · 14.2 UN proper shipping name | |
| · ADR | UN1263 PAINT RELATED MATERIAL |
| · IMDG, IATA | PAINT RELATED MATERIAL |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 3 (F1) Flammable liquids. |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | III |

(Contd. on page 8)

Trade name: AP-Merit 7525 Härter standard

(Contd. of page 7)

- | | |
|--|--|
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Hazard identification number (Kemler code): | 30 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | A |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Transport category | 3 |
| · Tunnel restriction code | D/E |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · UN "Model Regulation": | UN 1263 PAINT RELATED MATERIAL, 3, III |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	25-50

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
- **Classification according to Regulation (EC) No 1272/2008**
The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 9)

Trade name: AP-Merit 7525 Härter standard

(Contd. of page 8)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**